



Ware Cart EX Installation Instructions



CONGRATULATIONS! You have purchased the strongest and most versatile ceramic ware cart on the market. Since 1969, brent® products have earned a reputation for superior quality and unmatched product support. We constantly strive to improve our products so that they are always the best value for the money. AMACO® values your input and welcomes any comments you may have on our products and customer service. Call (800) 374-1600 and speak to one of our sales service representatives.

The Ware Cart EX includes the following features:

- Super-strong top/bottom frame supports that bolt into place
- Four heavy-duty, totally locking casters
- 9 shelf supports instead of the previous 8, making it more versatile
- Easy assembly — one person can assemble alone

Tools required for assembly:

- $\frac{7}{16}$ " open-end wrench
- Two $\frac{1}{2}$ " wrenches, may be open end or 6" adjustable

Before beginning assembly, please verify that all parts listed below are included:

<u>Item no.</u>	<u>Description</u>	<u>Qty.</u>
1.	Side frame	2
2.	Lower spreader tube	2
3.	Upper spreader tube	1
4.	Caster	4
5.	$\frac{5}{16}$ -18 x 2 bolt	8
6.	$\frac{5}{16}$ -18 x 1- $\frac{1}{2}$ bolt	4
7.	$\frac{5}{16}$ -18 nut	12
8.	Retaining plate	6

Continued on back

1. Lay one side frame on its back on the floor. If working on a concrete floor, it's a good idea to lay it on a piece of cardboard from the shipping carton so that the powder coated finish will not be marred.
2. Insert square spreader tube into receiver at top of frame and bolt loosely into place, inserting the bolts from the top of the receiver (when the ware cart is standing in its normal position bolts should point down). Be sure to install retaining plates under the nuts. Install the two rectangular spreader tubes in the receivers at the bottom of the frame in a similar manner, except that the bolt closest to the frame will be installed from the bottom of the receiver.
3. Next lay the remaining side frame in place on the spreader tubes and bolt loosely into place. Tighten all bolts by hand and verify that everything is assembled correctly up to this point, then tighten all bolts firmly.
4. Use a 7/16" wrench on the bolt head located just above the caster wheel. Hold the rubber stem of the caster and begin to tighten the bolt. This will mushroom the rubber stem section of the caster out and allow for a slightly snug fit into the tube of the ware cart frame end. You may need to repeat this process until the optimal amount of friction is applied to allow you to completely tighten the caster stem inside the frame end.
5. Assembly is now complete. Carefully stand the cart on its wheels.

If you have any questions about these instructions, call Brent® customer service/repair: (800) 999-5456.

SAFETY NOTICE

1. **NEVER** allow children to play in or on the ware cart. Serious injury can result from falls or from broken pottery shards. When moving the ware cart, always be sure that your path is not obstructed. Never roll the ware cart over an extension cord.
2. **NEVER** allow children to play with the protective plastic bag included with this Ware Cart. It is not a toy. Suffocation can occur if misused.
3. Because the shelves are made of wood, never leave the ware cart or shelves near a kiln, as temperatures outside the kiln during firing may be high enough to cause combustion.

PLEASE KEEP THIS INSTRUCTION SHEET FOR FUTURE REFERENCE.



American Art Clay Co., Inc.
6060 Guion Road, Indianapolis, IN 46254 USA
(800) 374-1600 • Fax: (317) 248-9300
brent Customer Service/Repair: (800) 999-5456
www.amaco.com • email: TechnicalSupport@amaco.com